COREFIX® KIT

FEATURES

- Complete wall fixing kit for all wall types
- Fixings for both medium & heavy duty loads
- Suitable for plasterboard, dot & dab, masonry & cavity walls
- Supplied in a handy organiser case

APPLICATIONS

- **Lighting fixtures**
- **Curtains**
- **Bathroom fittings**
- **TV brackets**
- **Electrical boxes**
- **Shelves & Cabinets**

CONTENTS

- **4 x Corefix Connect** Dot & Dab Fixings
- **2 x Corefix Spike** Self-Drilling Heavy Duty Plasterboard Fixings (x2)
- **8 x Corefix Twist** Self-Drilling Medium Duty Plasterboard Fixings (x8)
- **8 x Corefix One** Heavy Duty Universal Wall Plugs (x8)
- **8 x Corefix One** Medium Duty Universal Wall Plugs (x8)
- All fixings are supplied with the correct screws.

TECHNICAL DATA

	CONNECT	SPIKE	TWIST	ONE 6mm plug	ONE 8mm plug
Drill diameter (masonry)	10mm	n/a	n/a	6mm	8mm
Drill diameter (plasterboard)	10mm (dot & dab)	n/a	n/a	5.5mm	7mm
Min. hole drill depth	100mm	n/a	n/a	45mm	60mm
Screw diameter	5mm	5mm	4.5mm	4.5mm	5mm
Screw length	100mm	40mm	30mm	50mm	60mm
Screw material	Steel	Steel	Steel	Steel	Steel
Fixing length	95mm	44mm	31mm	36mm	51mm
Fixing material	Impact resistant PP copolymer	Die cast metal/ engineered nylon	Zinc Alloy	Plastic	Plastic
Max. fixture thickness	10mm	10mm	10mm	10mm	10mm
Safe Working Load - Dot & Dab (Shear, single fixing)	55kg	n/a	n/a	60kg	100kg
Safe Working Load - Masonry (Shear, single fixing)	55kg	n/a	n/a	60kg	100kg
Safe Working Load - Plasterboard (Shear, single fixing)	n/a	50kg	16kg	10kg	10kg

Notes: Factor of safety of 2. Data is for static loadings. Not recommended for cantilever brackets.

- Always check for cables and pipes before drilling and use suitable PPE.
- Always refer to manufacturer's instructions when installing anything with Corefix and use the recommended number of fixings.